

Chapter No.1 The users instructions	1
1.1 Safty	2
1.2 Operator training	3
1.3 Electrical and equipment safety	3
Chapter No.2 Electrical and equipment safety	
2.1 Features	4
2.2 Structure and performance of device	4
2.2.1 Structural composition	6
2.2.2 Specification of device	7
2.3 Treatment parameter reference	8
2.4 Accessories of device	8
Chapter No.3 Installation	9
3.1 Procedure of Installation	9
3.2 Installation Requirements & water input	5
3.2.1 Instruction of water input	6
3.2.2 Water circulation testing	7
3.2.2 Installation of operation handle	8
Chapter No.4 Software instruction	9
4.1Working display	9
4.1.1 Instruction of working display	10
4.1.2 Instruction of alarming indicator icon	11
4.2 System setting display	13
4.2.1Instruction of system setting display	14
4.2.2 Factory setting display	14
4.3 Software operation explanation	15
4.4 How to operate the device	18
4.5Treatment parameter reference	19

UK beauty machines -tattoo &hair re 4.6Attention after the treatment	
Chapter No. 5 Maintenance	22
5.1 Cleaning of device	22
5.2 Cleaning of operate handle &handle replace	22
5.3 System trouble shooting	22
Chapter No.6 Standard Rreturn to the factory for re	pairing

......26

UK beauty machines -tattoo &hair removal lasers Chapter No.1 The users instructions

Please read the user's manual carefully prior to operate the

machine! To make sure the device are in working status .Avoid unnecessary harm.Please read carefully of the peripheral unit manual ,if the operator want to connect the device to the other peripheral unit, or contact factory .

- Don't use the equipment with other electrical equipments.
- Don't operate the equipment when thunder weather, (In thunder weather, electric current will flow into the equipment and have an effect on normal power.)
- Don't put the equipment into the strong electric current and magnetic field, or will cause the fault.
- Verify room voltage with supply area of the equipment are consistent, Don't use alter-mating current more than 240V.
- Don't operate the equipment in the high temperature or humidity place, avoid cause electric shock or fault.
- Ensure that the equipment is connected with power supply prior to use.
- Prior to use, Ensure that connection is good between circuit and accessories.
- Avoid connecting in multi-plug socket.
- After connecting elect, the equipment need paying attention carefully.
- Don't shake or collide the equipment during the operation.
- Don't use the equipment if cable or connection are damaged, fall the ground, water, other damaged.
- Don't put the cover board and electric wire to be used as carrying handle.
- Electric wire and hose should get away from heat source.
- It's better to operate the equipment in the dry place, Don't use it outside the room.
- Only use our company to provide matching accessories.



- Please turn off power supply after use it, before cleaning and maintenance.
- Don't clean it with detergent, solvent or chemicals.
- Don't use the equipment when using aerosol products.
- Avoid water spraying on the equipment.
- Children under the age of 11, the disabled don't use the equipment alone, there must be someone to guide them.
- Children under the age of 7 doesn't use the equipment.
- Don't use the equipment if you are uncomfortable.
- Don't use the equipment if skin have any uncomfortable or hurt.
- Don't use it in the eye, glottis, genitals, oral cavity, ear , nasal mucosa and nipple etc..
- Pregnant women are forbidden to use it.
- Please consult doctor prior to use it if you have any questions.
- Never use the modified or remoulded equipment.
- Please wear professional goggle and glass before operate to avoid the light flash directly to eyes.

1.1 Safety

- The device is with self-testing function. When the device is turned on ,the system processor will self-test .Besides, during the device working period ,the system processor will self-test ongoing and intervals .
- When the emergency accident happened ,please press the emergency button (red button) to turn off the device .

Attention: The persons had accepted the distributors' training. They have the right to do the device inner maintenance. Otherwise, un-professional person made wrong maintenance may result the warranty in-valid.



1.2 Operator training

People who had accepted the professional training can use the diode laser device .Please ensure proper use our products, we recommend that you read this manual carefully prior to operate.Please . If the therapy is in the treatment process ,please identify with the words " relevant personnel no admittance".Before the treatment ,please clear the possible treatment risk to the patient .We suggest to make an agreement regarding the treatment . Treatment success or not mainly depends on the experience of the operator and understanding of professional knowledge.In the treatment process ,the therapy should wear the professional protection glass .The patient should take the professional goggle .The glass and goggle are both specially configured by device producer . Please do not wear the glass and goggle without professional advice.

1.3 Electrical and equipment safety

Equipment used in power source is 200 v to 240 v (50/60 hz) single-phase , International standards (CV 120 \sim 260 v, 50/60 hz); 20 a 50/60 hz) (90 \sim 130 v, single phase 3 line socket.

Device through three electric wires to contact the ground .Please make sure that the ground wire touch the ground totally . Only authorized person can repair the device ,other contrary repair or maintenance will result the warranty in-valid .

Attention: Strictly prohibit to use flammable items, such as acetone, alcohol. If disinfect the device by alcohol, please not turn no the device. Only when the alcohol evaporates completely, people will be allowed to use the device.



Chapter 2 Electrical and equipment safety

2.1 Features of device


DL808S is one device that can transform the electricity, light and heat to be one kind of continuous high energy laser. DL808S integrate the laser technology, lectronics technology and computer technology make a good performance on the permanent Hair Removal.

DL808S theory of hair removal: Diode Laser Hair Removal is the safest and fastest at the present. However, the primary chromophore for laser hair removal is melanin residing in the hair shaft. Secondly, melanin residing in the inner and outer root sheath may also act as a secondary chromophore. Based on selective photothermolysis principle, through specific wavelength, penetrate epidermis into dermis, optical energy was absorbed and translated into heat energy with restraining hair follicle tissues, and produce photothermal effect. It takes laser energy in hair follicle with rich in melanin, surrounding tissues absorb less even no energy, reach to restrained melanin of hair follicles and remove hair. Meanwhile, don't hurt around tissues and virtually pain-free remove surplus hair; eventually, reach to permanent Hair Removal.

2.2 Structure and performance of device

Through 2-2-1, DL808S is mainly composed of machine, control system and treatment handle.Control system including emergency button ,key switch ,control screen;

Control screen is 10.4 inch color touch screen. The treatment handle is the laser handle.



2-2-1 picture



2.2.1.1 Main machine

DL808S main machine Composition as below:

Power Module: Supply the electric to the whole machine.

Control system module: As DL808S CPU , carry out the different task by accepting information input , then as operator's order to output the real function .

Display screen module: Display the system information ,and accept the operator's working demands .

Cool system module: Water circulation +semiconductor +crystal sapphire three heat transfer ways to lower down the machine temperature to keep a long working time.

2.2.1.2 Control system

DL808S control system mainly composition as below:

Switch key:Turn on /off machine

Emergency button:Turn off machine immediately when there are accident or abnormal appeared .To protect machine safe .

Display screen: Input and show the system setting.

Foot switch: Step down the foot switch ,device will be on; Released the foot switch ,the device will be off .

2.2.1.3 Treatment handle

Treatment handle is main implementation of treatment, including pipe, head. The electrical wire and data line are all in the pipe. Picture 2-2-2 is the treatment handle.





Picture 2-2-2

2.2.2 Specification of device

Form 2-2-1 Specification of device

Specification	Data
Light source	Diode laser
Laser emitter	12bar/720W/50A
Wavelength	808nm±10%(1064nm 755nm)
Electrical current	15-50A
Energy density	1-140J/cm ²
Frequency	1-10Hz
Width of light	10-400ms/±10%-40%
Light output size	1.4*1.4
Cooling system	Close-cycle water cooling; fan



	cooling and semi-conductor cooling
Operator display screen	10.4" TFT True Color LCD

2.3 Treatment application

DL808S used for permanence hair removal

2.4 Accessories of Device

Accessories list of DL808S as below

Form 2-4-1 Accessories list of DL808S

Name	No.	Name	No.
User manual	1	Power line	1
Treatment handle	1	Foot switch	1
cross screwdriver	1	Funnel	1
500ml measuring glass	1	Therapy glass	1
goggle	1		



UK beauty machines -tattoo &hair removal lasers **Chapter 3 Installation**

3.1 Procedure of Installation

Before unpacking the machine, ensure that working environment conforms to the requirements of this section The device should be place in the environment without etchant gas, less dust, etc. The etchant gas will make a bad destroy to the wires, Equipment of the electronic and optical components. Dust in the air will make a badly destroy to the filters and electronic components. The equipment installation environment temperature and humidity range should be accord with the requirement.

After unpacking the parcel, before installing the device, ensure that the device keeps the cool ,clean and dry place for 12 hours, in order to avoid destruction by high humidity during long distant transportation. Avoid the machine working in dusty dirty environment. That will make bad influence on the inner electric parts.

- Procedure of Installation:
- Unpacking the device. Checking whether all the accessories are all correct.
- Staying the device for 24 hours, in order to avoid destruction by high humidity during long distant transportation.
- Assembly of its components and ensure that all connections are firmly in place. Then connect electric and foot switch, do the water circulation testing.
- Fill the water tank with distilled water only.
- Make sure every parts and accessories are connected firmly and correctly then turn on device , testing the functions and parameters .
- If every above are all proper, treatment procedure is available.

3.2 Installation Requirements & Install the handle& water input


Before operate the machine, please fill distilled water. Every time before operation or

turn on the machine ,Please check the water measure to be sure there are enough water (90% of the water meter line) Otherwise ,please fill the distilled water .

3.2.1 Installation of operation handle

When customer install the treatment handle. Please put the handle lower than main device ,aim to let the gas out from the handle .

• Picture 3-2-1 ,take the handle connector to the device , First press the buttons on both sides of the handle (D1 D2), Align A1A2, B1B2, C1C2, and then firmly install the handle .When there are "kaka" sound (or D1D2 pops up) ,the connect work finished.




Picture 3-2-1

Note: If you replace the handle, before installing the handle again, be sure to wipe clean the water droplets on the connector, otherwise it is easy to burn out the power supply


After the handle installation, let the device turn on about one minute, keep the water circulation enough .

3.2.2 Instruction of water input


Note: Must use distilled water



- The temperature of the environment should be 5° C ~40°C; Humidity should lower than 80%, the Therapy room should be clean.
- Please keep the "water overflow" hole open ,when people input water, otherwise the water input is unavailable.(picture 3-2-2) Please keep the treatment handle installed proper (3.2.1 handle installation)



- Connect the funnel to the plastic pipe ,then put another end of plastic pipe into the water in hole (picture 3-2-2). Input distilled water by funnel . When there are water overflow ,the water inputting is finished .
- After the water input, press the black metal plate while the water input pipe remove .(picture 3-2-3)



Picture 3-2-3


• If you need to change the water (generally it is recommended to drain the waste water from the machine work in 1-3 months), please open "water in" while "water discharge", then waste water will flow out of the "water discharge" hole, please prepare the basin in advance. Please out put the old or dirty water as more as possible.

UK beauty machines -tattoo &hair removal lasers 3.2.3 Water circulation testing

Please connect the foot switch when operator finish the water input and power electric wire connect. Please testing the water circulation as below:

- Please make sure the emergency button " is up before turning on the machine.
- The circuit breaker " is behind the machine .Please turn the circuit breaker on
- Turn on the key " ,the water circulation will be working automatically .

Please observe whether the water circulation working normal or not. If there are no water leaking or water circulation alarming, please let the machine to be working one min, then turn off the machine.



Picture 3-2-4

• When customer want to take off the handle, Please press the button up and down, then pull the handle.



UK beauty machines -tattoo &hair removal lasers **Chapter 4 Software instruction**

4.1 Working display

4.1.1 Instruction of working display

Picture 4-1-1 Instruction of working display

	Icon Name		Function
User Settings button	*	System Settings frame	Enter into the factory setting display
		Water temperature frame	show water tank water current temperature
		Treatment handle temperature frame	Show the treatment handle temperature
	-25	Water flow frame	Show the current water flow status
	77	Water level frame	Red color show water lacking ,green color show normal
	J/cm²	Energy density frame	Show the current energy density
		Sound icon	Sound attention
	•	Ready button	Ready to work



Picture4-1-2

4-1-2 Instruction of working display

	Icon	Name	Function		
User Settings button		Water temperature alarm icon	When the water in the tank temperature is higher ,there will be "!" icon show.		
		Handle temperature alarm icon	When the handle temperature value is too high "!" marker will appear		
	<u> </u>	Water flow alarming	When the water flow frame show the value is too high .The "! "marker will appear		

4.1.2Instruction of alarming indicator icon

4.1.2.1 Water level alarming

When the water level alarming icon show red color ,and "!" marker is appeared ,that is mean the water is too less .

Solution : please input water in time.

4.1.2.2 Water tank temperature alarming

Water tank temperature value is too high ,and the "! "marker is appeared ,the system will switch to the standby status automatically .

Solution:Please check whether the water circulation component working normal or not ,or whether there are any destroy or broken of the components .If all above problems are not happen.Please contact the device producer or distributor .

4.1.2.3Treatment handle water temperature alarming

Treatment handle temperature value is too high ,and the "! "marker is appeared ,the system will switch to the standby status automatically .

Solution:Please stop to use the treatment handle and wait some time, then turn on the device again. If the handle temperature alarming is continue, please contact afterservice engineer or your distributor.


4.1.2.4 Water flow alarming

When the water flow icon value smaller than "2" and the water drop icon is lighted ,that is mean the water flow alarming ,The device system will switch to the standby status automatically .


Solution: Check up the water level to see whether there are enough water . Please check up the treatment handle connect well or not . Whether there are water leaking . If all above problems are not happen. Please contact the device producer or distributor .


4.2The software interface introduction

4.2.1Hair removal(Smart Mode)










4-2-1

Press the hair removal, get into the mode option interface, using the smart mode, choice male/female, decide the treatment area, the clinic data will be auto generated. Press working.

4.2.2Hair Removal (Expert Mode)








4.2.2

Press the hair removal, get into the mode option interface, using expert mode, the operator base on the customers' situation, setting the parameters. Press the working.

4.2.3 Skin Rejuvenation Interface



4.2.3

Get to the skin rejuvenation, the clinic data will be auto generated, press working.

4.2.4Instruction of system setting display

Picture 4-2-1 Time date setting list

Icon	name	Function	Remarks

	language set	Language	——
	tings	option	
- Qo	Value	Max value	
	limitation	and alarming value	
राम	Alarming	Record	
	record	alarming	
6	Safe setting	Safe setting	

4.3 Software operation explanation

4.3.1 Parameter setting

Touch the value display frame, the number enter board will pop-up, customer will be able to enter the number or value . Touch the delete button to cancel the wrong entering . Touch enter button to finish the information input. Touch the save button to record the parameters .

4.3.2 Standby/Ready switch

When the system in "Standby" status ,press "Ready" button the device will switch to the "Ready" status . When the system in "Ready" status ,press "Ready" button the device will switch to the "standby" status .When the device is in the "standby" status ,the handle indicator light will be in yellow color ,when the device is in the "Ready" status, the handle indicator light will be in green color .

4.4 Treatment procedure and How to operate the device

 Prior to treatment, the physician must first get a detailed history, rule out any disorders that may contraindicate this treatment and finally physically inspect the treatment area. (Especially regarding the dark skin patient ,we suggest doctor to

UK beauty machines -tattoo &hair removal lasers make the inspect testing before the treatment)

- Before do the treatment please make a communication .Please Shave the hair ,then clean the treatment place by neutral cleaner .Please not use any cosmetics .Then smear 1 to 2 mm get .
- Turn on the device ,enter into the parameter setting display .
- Setting proper parameter regarding different patients .Press "Standby /ready "button into the working status .
- When the device is in the standby status ,the handle indicator light will be yellow color .When the device is in the Ready status ,the indicator light will be green .When therapy press the handle button ,the indicator light will be in red color .
- During the treatment ,therapy should adjust the parameter regarding the patient's feedback.
- During the treatment ,the handle should not stay long time in one treatment place; Please take glass and goggle to avoid risk.
- Turn off the power supply after the treatment ;remove the gel ,cool down the treatment place .The cold compress can be done when the device is in Standby status .
- Clean the head of treatment handle by warm wet towel .Then use the cotton ball pick up the disinfectant to clean the head again .
- After the disinfectant ,please place the treatment handle into the professional box .Turn off the power supply ,finish the treatment .

UK beauty machines -tattoo &hair removal lasers 4.5 Treatment parameter setting reference

4.5.1 Smart mode---hair removal (Male)

				Smart Mod	e (Hair Remo	val)		
	Area	HZ	Skin type	Energy reference	Area	HZ	Skin type	Energy reference
	. (false		Type I	30-40			Type I	35-45
	ALC:		Type II	28-38	a P		Type II	33-43
	20	2-4hz	TypeIII	26-36		5-8hz	TypeIII	31-41
	(e)	2-4112	TypeIV	24-34	1	3-0112	TypeIV	29-39
	Face		Type V	22-32	Chest		Type V	27-37
	race		TypeVI	20-30			TypeVI	25-35
60		3-5hz	Type I	28-38	3-5hz	3-5hz	Type I	33-43
Male			Type II	26-36			Type II	31-41
Wale			TypeIII	24-34			TypeIII	29-39
G			TypeIV	22-32			TypeIV	27-37
			Type V	20-30			Type V	25-35
			TypeVI	18-28			TypeVI	23-33
	E	En U	Type I	45-55	19/		Type I	55-65
	arc		Type II	42-52	14 07		Type II	52-62
	MILL STEP	4-7hz	TypeIII	40-50		5-8hz	TypeIII	48-58
	-	4-/nz	TypeIV	38-48		J-011Z	TypeIV	45-55
	Arms		Type V	34-44	Legs		Type V	42-52
	12/113		TypeVI	31-41			TypeVI	39-49

4.5.2 Smart mode---hair removal (Female)

	Area	HZ	Skin type	Energy reference	Area	HZ	Skin type	Energy reference
Ī			Type I	35-45			Type I	40-50
			Type II	32-42	EC		Type II	38-48
	0 0	2-4hz	TypeIII	30-40	Mary 1	5-8hz	TypeIII	36-46
		2-4112	TypeIV	27-37	1	5-0112	TypeIV	34-44
	Face		Type V	25-35	Abdomen		Type V	32-42
			TypeVI	22-32	Abdollieli		TypeVI	30-40
E	*	3-5hz	Type I	33-43	Bikini		Type I	38-48
	E.		Type II	31-41		3-5hz	Type II	36-46
Female	Female		TypeIII	28-38			TypeIII	34-44
			TypeIV	26-36			TypeIV	32-42
			Type V	24-34			Type V	30-40
			TypeVI	22-32			TypeVI	28-38
	15		Type I	50-60			Type I	60-70
	100		Type II	47-57	6		Type II	57-67
		4-7hz	TypeIII	45-55	400	E Obe	TypeIII	53-63
	111	4-/112	TypeIV	42-52		5-8hz	TypeIV	50-60
	Arms		Type V	39-49	Legs		Type V	47-57
			TypeVI	36-46	2083		TypeⅥ	43-53

UK beauty machines -tattoo &hair removal lasers 4.5.3 Skin rejuvenation

	Skin Rejuvenation Mode						
Treatment area	Frequency	Energy reference j/cm²					
Face	3-5hz	28-38					
Arms	4-7hz	32-42					
Chest	3-5hz	28-38					
Back	5-8hz	35-45					
Abdomen	4-7hz	32-42					
Legs	4-7hz	35-45					

4.6 Attention after the treatment

- During the treatment ,please not stay the handle in one place long time.
- Please use the soft neutral cleaning products and warm water to clean skin
- Use moisture face masker to supply more water to the skin.
- Use the VC cream or neutral moisture cream to protect the skin .
- Please use the sun cream not less than SPF 30
- In one month after the treatment please use high SPF sun cream and avoid sunburnt .Because strong sunshine will prove the hyperpigmentation happened .
- Within 24 hours after treatment to avoid using hot water to take shower ,avoid to use antiperspirant,avoid to swimming in the pool with High chlorine.
- A light make-up is available after the treatment ,But the operator suggest to stop the make-up ,once there are any destroy or infection and contact your beautician or doctor to help you .



• After the treatment ,therapy can use the handle to cool down the skin 5 to 10 minutes. The machine should be in standby status when do the cooling.

Chapter 5 Device Maintenance

5.1 Main device cleaning

Please use soft wet cloth to clean the main device, to avoid liquid into the device.

5.2 Operate handle cleaning and replace

- Clean the handle light output place after the treatment, because during the treatment, some pigment granules maybe splash to the crystal, that will be lower the laser output energy. We suggest to use the lens paper to clean. Or the use absolute alcohol to clean.
- Every treatment handle are all with working life .After using half a year (around 100,000,000 times) ,we suggest the customer to replace a new handle .Please contact your distributor or device factory .

5.3 System trouble shooting

5-3-1 System trouble shooting

Trouble Phenomenon	Solution
Screen without display	Check the electric wire
	Check the circuit-breaker, fuse wire
	Please check the power supplier switch
	Please contact the distributor or device producer
No reaction of	Please check whether the power supply switch
the handle	behind the device is on or not .If on ,the trouble is

switch	still ,please contact the distributor or device	
button ,and no	producer	
reaction by key		
System can not	Check the power supplier	
be initialization	Please contact the distributor or device producer	
The energy	The voltage is too lower result the handle can not	
	work normally	
	Please check whether there are dirty thing on the	
	laser reflective mirror ,if yes ,please clean it .	
	The handle inner is destroyed ,please replace new	
	treatment handle	
output lower or	Disassemble the treatment handle to check	
no laser output	whether the head reflective mirror are destroyed	
	or not.	
	The treatment handle is too hot ,please turn off	
	the machine ,cool down around 30 minutes ,then	
	use again .	
	Please check the handle water leaking or not .	
Treatment		
handle dropped	Please check the handle destroyed or not ,if	
out of the handle	yes ,please replace new handle .	
holder		
During the	The device is not turned on for too long time .It is	
treatment .when	hard to motivate.	

therapy press	The treatment room temperature is too
the handle	lower ,please higher the room temperature .
button ,there are "zizi "noise	Please check the electric of the device normal or not
	The humidity of the treatment room is too
	higher .Please lower the room humidity.
Cooling system temperature is too	Turn off the device minutes ,then return on
	again .If the cooling system is still
	abnormal ,please contact distributor or device
	producer
The treatment handle output energy is too lower	Please check whether there are dirty thing on the
	reflective mirror ,If yes please clean it .
	If the handle is hot ,please turn off the machine 30minutes
	Please check the head of the reflective mirror
	good or not ,if there are any destroy .Please
	contact your distributor or device producer.
The treatment	
handle output	Treatment head the working life is over.Please
energy is too	contact your distributor or device producer.
lower	
Laser emitter is broken	Please contact your distributor or device producer.

UK beauty machines -tattoo &hair removal lasers Chapter 6 Standard

This chapter details the most important technical parameters and treatment system of categories.

6-1 System standard list

Specification	item
◆ electrical connections	
data	
Electrical voltage	110/220VAC ±10%
Electrical frequency	50/60Hz
♦ Device type	
Against electric shock protection type	Type I
Against electric shock protection level	BF
Harmful water invade type	Normal
♦ Weather	
condition(during the	
operation)	
Temperature around	+15°C to +30°C
Relative humidity	30% to 80%
Atmospheric pressure	86.0 kpa to 106.0kpa

♦ Weather	
condition(during the	
transport of device)	
Temperature around	+5°C to +55°C
Relative humidity	30% to 80%
Atmospheric pressure	86.0 kpa to 106.0kpa
Dimension and weight	
Device length/packing	40cm /65cm
length	
Device width/packing width	35cm/63cm
Device height/packing	130cm/140cm
height	
Gross weight/net weight	54Kg/72Kg

Owing to the problem of equipment is properly work, and you has simple maintained it according to above methods, Equipment is still abnormal, please contact our after -sales service center.

After-service center phone: +44 7562 053547

Website link: https://ukbeautymachines.co.uk